



## ALTA QUALITÀ POWER IMPACT

 Articolo	 mm	LUNG. mm	Descrizione	
<b>112514</b>	0,8 X 5,5	41	INSERTO TAGLIO ATT.5/16°C MM.5,5 L.41	1
<b>12515</b>	1 X 6	41	INSERTO TAGLIO ATT.5/16°C MM.6 L.41	1
<b>12516</b>	1,2 X 6,5	41	INSERTO TAGLIO ATT.5/16°C MM.6,5 L.41	1
<b>112517</b>	1,2 X 8	41	INSERTO TAGLIO ATT.5/16°C MM.8 L.41	1
<b>12518</b>	1,6 X 8	41	INSERTO TAGLIO ATT.5/16°C MM.8 L.41	1
<b>112519</b>	1,6 X 10	41	INSERTO TAGLIO ATT.5/16°C MM.10 L.41	1
<b>112520</b>	2 X 12	41	INSERTO TAGLIO ATT.5/16°C MM.12 L.41	1
<b>112521</b>	2,5 X 14	41	INSERTO TAGLIO ATT.5/16°C MM.14 L.41	1

### Caratteristiche

ALTA QUALITÀ POWER IMPACT  
attacco: DIN 3126, C 8  
impronta: 5264-C