



MASCHI STI PER CANDELE A GRADINO CORTO, PASSO METRICO

 V-COIL THREAD INSERT SYSTEM		Metrico	L1	Diametro nominale D	P	B	L2	D2	B2	L3	Descrizione	
03630	6.3	M 6	70	M 6	x 1.0	7.3	28	8	6	7	MASCHIO FILETTI RIP. M 6 X 1.0 PER CANDELE	1
03631	6.3	M 8	75	M 8	x 1.25	9.6	32	8	8	9	MASCHIO FILETTI RIP. M 8 X 1.25 PER CANDELE	1
03632	7.1	M 10	80	M 10	x 1.5	11.9	37	9	10	9	MASCHIO FILETTI RIP. M 10 X 1.5 PER CANDELE	1
03637	6.3	M 10	74	M 10	x 1.25	11.6	30	8	10	8	MASCHIO FILETTI RIP. M 10 X 1.25 PER CANDELE	1
03633	6.3	M 10	74	M 10	x 1.0	11.3	30	8	10	8	MASCHIO FILETTI RIP. M 10 X 1.0 PER CANDELE	1
03634	7.1	M 12	75	M 12	x 1.25	13.6	32	9	12	9	MASCHIO FILETTI RIP. M 12 X 1.25 PER CANDELE	1
03635	9.2	M 14	90	M 14	x 1.25	15.6	45	12	14	10	MASCHIO FILETTI RIP. M 14 X 1.25 PER CANDELE	1
03636	12.5	M 18	116	M 18	x 1.5	20.0	47	16	18	10	MASCHIO FILETTI RIP. M 18 X 1.5 PER CANDELE	1

Caratteristiche

Maschi STI per candele a gradino corto
per filetti riportati ISO 2 (6H)
Passo Metrico
HSS-G Tolleranza ISO 1 (4H)